AFWSB Series


RoHS & REACH Compliant

ESD Fabric Wrist Straps are a low-cost solution for electronic assembly technicians. The set includes an adjustable wrist band with 4mm male snap and 12 ft. coil cord. The other end has a removable alligator clip/banana plug. The 2.4mm polyurethane coil insulation offers excellent coil memory.

Product Specifications (1)

Banana	Swivel Type
Туре	Coil Cord
Color	Blue
Material	Polyester with Stainless Steel Nylon
Resistor	1 Meg ohm (+/- 5% tolerance)
Size	Band = Adjustable; Cord = 12 ft. long
Outer Diameter	2.4mm (+/- 0.1mm)
Snap	4mm

(1) Specifications are subject to change at any time. If you have any questions, please contact us for the latest update.





Bertech[®] makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its this product for any particular purpose, nor does Bertech[®] assume any liability whatsoever arising out of the application or use of this product. It is ultimately the responsibility of the customer to determine a product's suitability for a particular application.



AntistaticMat

640 Maple Ave Torrance, CA 90503 Phone: (310) 787-0337 Email: sales@antistaticmat.net www.antistaticmat.net

PRODUCT DATA SHEET

AMWS Series


RoHS & REACH Compliant

ESD Metal Wrist Straps are a premium band set featuring a high quality adjustable, one size fits all metal wrist strap band with an insulating outer surface and a coil cord. The band is standard with 4mm, machined male snap and provides a 360° conductive contact around the wrist, providing maximum skin contact. A shorter, swivel type banana jack increases coil life, prevents cord tangles and fits most bench grounds. It is uses highly conductive copper sulfide nylon thread for conductivity and it has a maximum resistance of 160 ohms. Comes with a 12 ft. cord.

Product Specifications (1)

Banana	Swivel Type
Buckle	Black Metal Expansion Band
Color	Black
Resistor	1 meg ohm (+/- 5% tolerance)
Size	Band = Adjustable; Cord = 12 ft. long
Stud	4mm Stud
Expansion Ratio	1.5: 1

(1) Specifications are subject to change at any time. If you have any questions, please contact us for the latest update.





Bertech[®] makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its this product for any particular purpose, nor does Bertech[®] assume any liability whatsoever arising out of the application or use of this product. It is ultimately the responsibility of the customer to determine a product's suitability for a particular application.



AntistaticMat

640 Maple Ave Torrance, CA 90503 Phone: (310) 787-0337 Email: <u>sales@antistaticmat.net</u> www.antistaticmat.net

PRODUCT DATA SHEET